

# BAP Equipment Ltd

## Stream Flowmeters

### Basic Flowmeter

The Revolutions of the impeller are sensed electronically and transmitted to a hand-held counter unit that features start, stop, and clear functions. Revolutions per unit of time can be translated into stream velocity using a conversion chart. May be used in brackish water or salt water. Fitted with a re-settable LCD counter, this flowmeter eliminates the need for tiresome calculations. Comes complete with PVC pole mounted with an impeller which collapses into four sections for easy storage and carrying, three stream bed elevation rods, protective carrying pouch for counter, weather-proof storage case, instruction manual, and comparison charts. Materials: PVC impeller poles, stainless steel impeller shaft, plastic impeller. Dimensions: Overall pole length: 3.3'. Four individual sections: 9.8" each. Cable: 3.3'. Elevation rods: 9.8", 4.9", and 2.5". Data Readout: LCD counter; 800 counts per minute; re-setting. Sensor Type: Magnetic. Range: Approximately 0.05m/sec to 8.0m/sec. Accuracy:  $\pm 7\%$ . Power: 2 AAA batteries (included).



**BAP Equipment Ltd.**  
203 Waggoners Lane,  
Fredericton, N.B.  
Canada E3B 2L4

**Phone 1-800-561-3600**  
**Fax 1-800-452-0881**  
**Email: info@bapequipment.com**  
**Website: www.bapequipment.com**